GLORY

# CI-10X for the back office

Compact cash recycling system



Combining both a banknote and coin recycler, the CI-10X accelerates back office cash processes in locations where a compact cash automation solution is required. Delivering increased productivity and reducing the risk of cash shrinkage, CI-10X allows your staff to focus on higher value activities that improve customer experience and drive growth for your business.

Euro

## As part of the CASHINFINITY<sup>™</sup> solution, CI-10X offers an optimal balance between a footprint and cash recycling capacity, meeting the demands of small retail and gaming organisations.

	CI-10BX (banknote recycler)	CI-10CX (coin recycler)		CI-10BX (banknote recycler)	CI-10CX (coin recycler)
Dimensions (W × D × H)	Terminal Included UL-291 24-hours safe without monitor 340 × 720 × 935 mm (13.4" × 28.3" × 36.9") with monitor 340 × 720 × 1327-1457 mm (13.4" × 28.3" × 52.3"-57.4")	Terminal included without extension top cover with slide extension unit and spacer M $240 \times 485 \times 850 \text{ mm } (9.4" \times 19.0" \times 33.5")$ with extension top cover $270 \times 721 \times 935 \text{ mm } (10.6" \times 28.4" \times 36.9")$ Terminal separated for CI-10BX UL model with slide extension unit and spacer M $240 \times 485 \times 850 \text{ mm } (9.4" \times 19.0" \times 33.5")$ for CI-10BX Sheet-metal enclosure model $240 \times 485 \times 750-760 \text{ mm } (9.4" \times 19.0" \times 29.5"-29.9")$ with slide extension unit and spacer M $240 \times 485 \times 820-860 \text{ mm } (9.4" \times 19.0" \times 32.3"-33.9")$ with slide extension unit and spacer L $240 \times 485 \times 870-960 \text{ mm } (9.4" \times 19.0" \times 34.3"-37.8")$ Height can be adjusted	Dispensing Capacity of outlet: Speed of cash out: Capacity	10 notes <sup>1</sup> 3 notes / sec <sup>1</sup> 4 recycle modules 100 notes / recycle <sup>1</sup>	50 coins <sup>2</sup> 4 coins / sec <sup>2</sup> <b>Total 8 recycle stackers</b> (Stacker M: 8) 2 EURO 150 coins
	Terminal separated UL-291 24-hour safe 340 × 720 × 850 mm (13.4" × 28.3" × 33.5") Sheet-metal enclosure 240 × 485 × 750-760 mm (9.4" × 19.0" × 29.5"-29.9") with slide extension unit and spacer M 240 × 485 × 820-860 mm (9.4" × 19.0" × 32.3"-33.9")			Collection 300 notes <sup>1</sup> (interface cassette type) 450 – 360 notes <sup>1</sup> (collection cassette type)	0.1         EURO         200 coins           1         EURO         150 coins           0.05         EURO         200 coins           0.5         EURO         150 coins           0.2         EURO         250 coins           0.2         EURO         160 coins           0.01         EURO         350 coins
	with slide extension unit and spacer L 240 × 485 × 870-960 mm (9.4" × 19.0" × 34.3"-37.8") Height can be adjusted				*Each capacity is the volume of coins per stacker Coin overflow box: 1,800 coins <sup>2</sup>
	Separate terminal				Auto-refill cassette: 1,000 coins <sup>2</sup>
14/-:	340 × 435.6 × 389.5 mm (13.4" × 17.2" × 15.4")	Terminal Included	Total capacity	700 notes <sup>1</sup> (interface cassette type) 850-760 notes <sup>1</sup> (collection cassette type)	Dependent on recycle module
Weight	Terminal Included with monitor UL-291 24-hours safe 265.5 ka / 584 lbs	without extension top cover 55.8 kg / 123 lbs (with spacer M) with extension top cover 71.3 kg / 157.2 lbs (with spacer M) Collection cassette type including cassette <b>Terminal separated</b> 49.1 kg / 108 lbs	Function	<ul> <li>Encryption interface for enhanced data security</li> <li>Easy-to-understand error recovery animation</li> <li>Verification performed within the device, no cash exposure</li> </ul>	
	Collection cassette type including cassette Terminal separated			Reduced cash exposure with collection cassette.	Coin auto-refill to reduce replenishment time/cost.
	UL-291 24-hour safe 260.5 kg / 573 lbs			Banknote alignment function in the inlet, to avoid feeding errors.	with auto-refill cassettes.
	Sheet-metal enclosure 58.2 kg / 128 lbs 64.9 kg / 143 lbs (with spacer M)	5.5.8 kg / 123 lbs (with spacer M) 58.3 kg / 128 lbs (with spacer L) Collection cassette type including cassette	Terminal	Selectable PC Client OS (CONTEC PC) Server OS (CONTEC PC)	
	67.4 kg / 148 lbs (with spacer L) Collection cassette type including cassette		Supply voltage range	AC 100 V - 240 V (50/60 Hz)	AC 100 V - 240 V (50/60 Hz)
	Separate terminal 17.3 kg / 38.1 lbs		Current consumption	3.4 A~1.2 A	3.2~2.2 A
Recognition unit	Counterfeit detection Option: Fit/Unfit detection	Counterfeit detection	Approval	CE, UL safety, UL security (291-24H)	CE, UL safety
Deposit Capacity of inlet: Speed of cash in:	30 notes <sup>1</sup> 3 notes / sec <sup>1</sup>	50 coins <sup>2</sup> 5 coins / sec <sup>2</sup>	<sup>1</sup> Dependent on banknote quality. Capacities are for reference only and are not guaranteed. <sup>2</sup> The capacity of coins is calculated in 10 EURO cent. Specifications are subject to change without notice. Please read the instruction manual carefully to		

Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

## **Related solutions...**

#### CI-10X for Back Office with separate terminal

A separate terminal offers greater layout flexibility, suitable to back offices with limited space.



#### **CI-10X for Front Office**

Compact and high capacity solutions enabling automated cash handling at point of sale positions.



### **CI-SERVERX**

Centralised management of cash throughout a store in the front and back office.



#### Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

The additional content of the additional co

DS-CI-10X-BO-EURO-1023 1.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin guality and process used. GLORY, CASHINFINITY and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2023.