

CI-10X for the back office

Compact cash recycling system



Combining both a banknote and coin recycler, the CI-10X accelerates back office cash processes in locations where a compact cash automation solution is required. Delivering increased productivity and reducing the risk of cash shrinkage, CI-10X allows your staff to focus on higher value activities that improve customer experience and drive growth for your business.



As part of the CASHINFINITY™ solution, CI-10X offers an optimal balance between a footprint and cash recycling capacity, meeting the demands of small retail and gaming organisations.

	CI-10BX (banknote recycler)	CI-10CX (coin recycler)
Dimensions (W × D × H)	Terminal Included UL-291 24-hours safe without monitor $340 \times 720 \times 935 \text{ mm} (13.4" \times 28.3" \times 36.9")$ with monitor $340 \times 720 \times 1327-1457 \text{ mm} (13.4" \times 28.3" \times 52.3"-57.4")$ Terminal separated UL-291 24-hour safe $340 \times 720 \times 850 \text{ mm} (13.4" \times 28.3" \times 33.5")$ Sheet-metal enclosure $240 \times 485 \times 750-760 \text{ mm} (9.4" \times 19.0" \times 29.5"-29.9")$ with slide extension unit and spacer M $240 \times 485 \times 820-860 \text{ mm} (9.4" \times 19.0" \times 32.3"-33.9")$ with slide extension unit and spacer L $240 \times 485 \times 870-960 \text{ mm} (9.4" \times 19.0" \times 34.3"-37.8")$ Height can be adjusted Separate terminal $340 \times 435.6 \times 389.5 \text{ mm} (13.4" \times 17.2" \times 15.4")$	Terminal included without extension top cover with slide extension unit and spacer M 240 × 485 × 850 mm (9.4" × 19.0" × 33.5") with extension top cover 270 × 721 × 935 mm (10.6" × 28.4" × 36.9") Terminal separated for CI-10BX UL model with slide extension unit and spacer M 240 × 485 × 850 mm (9.4" × 19.0" × 33.5") for CI-10BX Sheet-metal enclosure model 240 × 485 × 750-760 mm (9.4" × 19.0" × 29.5"-29.9" with slide extension unit and spacer M 240 × 485 × 820-860 mm (9.4" × 19.0" × 32.3"-33.9" with slide extension unit and spacer L 240 × 485 × 870-960 mm (9.4" × 19.0" × 34.3"-37.8" Height can be adjusted
Weight	Terminal Included with monitor UL-291 24-hours safe 265.5 kg / 584 lbs Collection cassette type including cassette Terminal separated UL-291 24-hour safe 260.5 kg / 573 lbs Sheet-metal enclosure 58.2 kg / 128 lbs 64.9 kg / 143 lbs (with spacer M) 67.4 kg / 148 lbs (with spacer L) Collection cassette type including cassette Separate terminal 17.3 kg / 38.1 lbs	Terminal Included without extension top cover 55.8 kg / 123 lbs (with spacer M) with extension top cover 71.3 kg / 157.2 lbs (with spacer M) Collection cassette type including cassette Terminal separated 49.1 kg / 108 lbs 55.8 kg / 128 lbs (with spacer M) 58.3 kg / 128 lbs (with spacer L) Collection cassette type including cassette
Recognition unit	Counterfeit detection Option: Fit/Unfit detection	Counterfeit detection
Number of recycle modules		8 recycle modules
Capacity	100 notes / recycle ¹	For your currency information, please contact your local GLORY office.

	CI-10BX (banknote recycler)	CI-10CX (coin recycler)
Coin overflow box capacity	-	1,800 coins ²
Auto-refill cassette capacity	-	1,000 coins ²
Collection capacity	300 notes¹ (interface cassette type) 450-360 notes¹ (collection cassette type)	-
Total capacity of banknotes/coins	700 notes¹ (interface cassette type) 850-760 notes¹ (collection cassette type)	Dependent on recycle module configuration
Deposit Capacity of inlet: Speed of cash in:	30 notes ¹ 3 notes / sec ¹	50 coins ² 5 coins / sec ²
Dispensing Capacity of outlet: Speed of cash out:	10 notes ¹ 3 notes / sec ¹	50 coins ² 4 coins / sec ²
Function	Efficient connections with your partners Dynamic "follow-me" LED guidance for deposit and dispense transaction Encryption interface for enhanced data security Adjustable slide extension unit / low slide extension unit. Easy-to-understand error recovery animation Verification performed within the device, no cash exposure	
	Reduced cash exposure with collection cassette. Banknote alignment function in the inlet, to avoid feeding errors.	Coin auto-refill to reduce replenishment time/cost. Optimise collection processes with auto-refill cassettes.
Terminal	Selectable PC Client OS (CONTEC PC) Server OS (CONTEC PC)	
Safe	UL-291 24-hour	-
Supply voltage range	AC 100 V - 240 V (50/60 Hz)	AC 100 V - 240 V (50/60 Hz)
Current consumption	3.4 A~1.2 A	3.2~2.2 A
Approval	CE, UL	CE. UL

¹ Dependent on banknote quality. Capacities are for reference only and are not guaranteed.

Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CI-10X for Back Office with separate terminal

A separate terminal offers greater layout flexibility, suitable to back offices with limited space.



CI-10X for Front Office

Compact and high capacity solutions enabling automated cash handling at point of sale positions.



CI-SERVERX

Centralised management of cash throughout a store in the front and back office.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

 ★ +44 (0)1256 368000
 Sales enquiries +44 (0)844 811 2006
 Info@uk.glory-global.com
 Info@uk.glory-global.com

DS-CI-10X-BO-GENERIC-1023_1.0

² The capacity of coins is calculated in 10 EURO cent.