

GLORY

## RBG-208

Teller cash recycler

Whether you're looking to transform your branches or simply improve efficiency for increased profitability, the RBG-208 will support your strategy. Enabling open plan layouts, reduced start / end of day processes, faster teller transactions, redeployment of staff and enhanced customer experience – the RBG-208 delivers.



## RBG-208 teller cash recyclers deliver an intuitive, secure, flexible and integrated teller automation solution to address the real needs of your customers and staff.

- **8 Roll storage modules** with a capacity of up to 600 banknotes each.
- Increased processing speed for large deposits without interruption thanks to a unique continuous feed hopper.
- Simultaneous processing of different currencies.
- Wide variety of safes, locks and alarm equipment to meet your specific security requirements.
- Regular upgrades and testing to national and international banking requirements and standards.
- Optional collection cassette with a capacity of around 2,000 banknotes.
- Serial number recognition allowing deposited notes to be tracked and the usage of the RBG-200 as a customer operated device.

<b>Features</b>	8 roll storage modules (RSM) Up to 600 notes per RSM Input hopper capacity: Max. 300 notes with continuous feed Output hopper capacity: Max. 150 notes Built-in fitness sorting
<b>Safe</b>	UL 291
<b>Lock</b>	LaGard 39E Standard
<b>Alarm</b>	Prepared for alarm integration
<b>Options</b>	CEN L / III / IV safe 2 additional RSMs or collection cassette Colour touch panel user interface Serial number recognition Alarm

<b>Speed</b>	Deposit: 7 notes per second Dispense: 6 notes per second
<b>Power consumption</b>	Sleep Mode: 72 Watt Standby: 120 Watt Withdrawal: 720 Watt Deposit: 720 Watt
<b>Noise emission</b>	Standby: 50.0 dBA Withdrawal: 67.7 dBA Deposit: 67.7 dBA
<b>Power supply</b>	100 – 240 V, 50/60 Hz
<b>Dimensions (H x W x D)</b>	RBG UL 291: 844 x 420 x 1046mm
<b>Weight</b>	RBG UL 291: 350 kg maximum
<b>Environmental conditions</b>	Operation: +5° to +35° Celsius 20% to 80% relative humidity Transport and storage: -5° to +45° Celsius 10% to 80% relative humidity

\*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.



This mark indicates the product meets Glory's environmental standards.

## Related solutions...

### CashInsight™ Assure

CashInsight Assure facilitates the operation of cash handling devices, providing immediate teller productivity.



### UBIQULAR™ Bridge

Continuous performance monitoring and remote device management solution.



### RCW-100

A compact coin recycling system, enabling automated cash handling at teller positions.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

+44 (0)1256 368000 Sales enquiries +44 (0)844 811 2006 info@uk.glory-global.com [glory-global.com](http://glory-global.com)

DS-RBG208-0721\_5.1

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, CashInsight, UBIQULAR and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2021.