GLORY

NMD100

Notes and media dispenser

With the lowest reject rate on the market, the Glory NMD100 guarantees maximum uptime and consistent, front or rear delivery of up to 100 banknotes per bundle. Offering up to eight cassettes, each holding up to 3000 notes, the NMD100 provides extensive functionality and flexibility for your customers wherever they are deploying your solutions.



A high capacity module with proven reliability, the Glory NMD100 minimises overall ATM servicing costs for your customer and provides maximum efficiency.

Front or rear access bundle delivery – With easily reconfigurable front or rear service application, the NMD100 reduces stock holding costs and simplifies inventory management. Flexible integration options minimises servicing costs and increases availability.

Cassette flexibility – The NMD100 offers eight high capacity cassettes, each holding up to 3000 notes each. Each cassette can be individually replenished and is available in several formats. This ensures increased ATM uptime and CIT collection efficiency, as well as delivering complete flexibility and ease of integration to your customers. For increased efficiency, a sealable reject vault or tray is also available.

Intelligent Double Detection IDD™ – Offers unbeatable accuracy and consistent detection of doubles even with severely degraded notes. No mechanical adjustments or intervention necessary.

High Performance Feed HPF™ – Provides consistent and durable feeding, reliable handling of notes of all conditions and the ability to process notes without causing damage.

The NMD100 is designed in accordance with the recommendations of leading International Standards Organisations including RoHS, UL, CE and UKCA to allow for final approval when installed in complete systems.

Speed range	7 – 8 notes per second
Document size range	Width: 58 – 92 mm
	Length: 100 – 181 mm
	Thickness: 0.06 – 0.32 mm
Maximum transaction size	100 ATM fit banknotes
Capacity	1 to 8 cassettes configurable
	Short cassette: 240 mm or 2000 banknotes
	Long cassette: 340 mm or 3000 banknotes
	A separate reject cassette: 250 banknote

Connectivity	RS232C connection as standard
Connectivity	Integrated shutter interface to control your own shutter
	Option: plug and play shutter
Power supply	120 – 240V AC, 50/60 Hz, 3A
	Fitted with integrated power supply
Operating environment	Temperature: 5–50°C, 41–122°F
	Relative humidity: 10–85% non-condensing
	*operating time above 45 degrees should be limited to less than
	10% of product life
Dimensions ($H \times W \times D$)	530* × 292 × 549 mm
	*height shown for 2 denomination with 85 mm throat extension, for
	each additional denomination add 128 mm
Throat extensions	Standard configuration 85 mm
	Throat extension kits for 130, 180 and 320 mm available
	(for rear service only)
Weight (without notes)	Standard 2 denomination with cassettes: 22.2 kg/48.9 lbs
0	Additional denominations
	Without cassette: 3.0 kg/6.6 lbs
	Short cassette (optional): 2.2 kg/4.9 lbs
	Long cassette (standard configuration): 2.9 kg/6.4 lbs
	Reject cassette (standard configuration): 2.0 kg/4.4 lbs
	Reject Box (optional): 1.0 kg/2.2 lbs
Manufacturing standards and approvals	, , , , ,
Manufacturing standards and approvals	NUTIO, UL, UE, UNUA

*Based on new issue banknotes, circulated notes will reduce capacity. The performance of polymer notes may reduce at extreme temperature and humidity combinations. Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by Glory Global Solutions (International) Limited. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

InstaChange™
A fast, accurate and secure
means to automatically return
change to customers.MultiMech™
Secure
and protection of cash.MultiMech™
Secure
to automatically return
and protection of cash.MultiMech™
Secure
to automatically return

Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

🗟 +44 (0)1256 368000 Sales enquiries +44 (0)844 811 2006 ĭ info@uk.glory-global.com 🕀 glory-global.com

DS-NMD1000EM-0823_3.1

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, HPF, IDD, InstaChange, MultiMech and their associated graphical representations (International) Limited 2023.