

GLORY

SDD

Single denomination dispenser

The Single Denomination Dispenser SDD combines high performance, compact size and low cost of ownership; making it the ideal choice for your self-service automation solutions. Available in four variants including front or rear service and standard or short builds, you can select the option that best suits your requirements.



An ultra compact and secure module with proven reliability and tamper indicating feed cassettes designed to deliver high levels of availability.

Unique Glory Technology

Intelligent Double Detection, IDD™, provides unbeatable detection of doubles even when notes are severely degraded. This increases the transaction performance and operational efficiency your customers require. No mechanical adjustments are required – IDD is ready to use straight out of the box.

Cassettes

The SDD features secure, tamper indicating feed cassettes with an integral reject note compartment.

Speed range	5 notes per second
Document size range	Width: 57 – 98 mm Length: 110 – 192 mm Thickness: 0.07 – 0.15 mm
Maximum transaction size	50 ATM fit notes
Capacity	Standard options: 260 mm or 1650 – 2150 banknotes Short options: 117 mm or 700 – 900 banknotes
Loading frame	Loading frame must be used to open the cassette and ensures correct loading of documents
Connectivity	RS232C, RS485, TTL serial interface with polling or handshake control as standard

Power supply	Operates from DC-only supply* requiring: 5V DC ±0.2V Max load current 1.5A 36V DC ±2V average Max load current 5A *Power supplies are available from Glory
Operating environment	Temperature: 5 – 50°C, 41 – 122°F Relative humidity: 10 – 85% non-condensing
Dimensions (H x W x D)	1700: 223 x 339 x 427 mm 1701: 223 x 339 x 274 mm 1702: 278 x 339 x 427 mm 1703: 278 x 339 x 274 mm Height of note outlet: 1700/01: 187 mm 1702/03: 242 mm
Weight (without notes)	1700: 8.5 kg/18.7 lbs 1701: 7.0 kg/15.4 lbs 1702: 10.0 kg/22.0 lbs 1703: 8.8 kg/19.4 lbs
Manufacturing standards and approvals	Designed in accordance with RoHS, UL and CE

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by Glory. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

MINIMECH™

An efficient, easy to maintain, single demonination mechanism offering a compact footprint.




MULTIMECH™

Easily integrated into almost any self-service solution, the MultiMech offers increased capacity with two cassettes.



MULTIMECH™ SECURE

The MultiMech Secure offers key locked cassettes to provide unrivalled security and protection of cash.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

+44 (0)1256 368000 info@uk.glory-global.com glory-global.com

DS-SDDOEM-0417_1.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY is a registered trademark of GLORY LTD. in Japan, the United States of America, and EU. All trademarks are owned by the GLORY Limited Group of companies. © Glory Global Solutions (International) Limited 2017.