GLORY

CASHINFINITY™ CI-X SERIES

Connecting your cash processes



CASHINFINITY™ AN INNOVATIVE SOLUTION FOR THE RETAIL INDUSTRY

While improving efficiency and cost reductions remain top-of-mind for retailers, there are also compelling reasons to transform the in-store experience in order to remain relevant and gain advantage in today's competitive world.

CASHINFINITY brings previously siloed elements of the cash journey together to deliver a joined-up result.

With disparate processes now operating in harmony, the results are organisation-wide efficiencies, cash safety, enhanced ROI and opportunities to drive new revenue streams through enhanced staff productivity.

Process efficiency, security, hygiene and managing queues are all unique challenges; what would it be worth to your business if these challenges could be solved?



CI-X SERIES IMPROVES CUSTOMER CONVENIENCE AND STORE EFFICIENCY, WHILE MAINTAINING CASH TRANSACTION FLOW, SECURITY AND SIGNIFICANTLY IMPROVING CASH MANAGEMENT ACCURACY.

CASH MANAGEMENT SOFTWARE

Optimises cash handling activities throughout the front and back office. Allows store managers to receive real-time device updates, status information and manage devices remotely.

BACK OFFICE SOLUTION

65

CI-X back office solutions enable a multitude of flexible operational processes to be implemented, allowing staff to focus on other activities that improve customer experience and drive growth for your business.

FRONT OFFICE SOLUTION

Removes the need for staff to handle cash at the point-of-sale. Automating cash handling minimises the risk of errors and shrinkage while enhancing staff productivity and customer service.

FRONT OFFICE SOLUTION

The right solution for any store or cash automation requirement

- With a renewed design that enhances operability for staff and customers, the CI-10X cash recycling solution removes the need for staff to handle cash at the point-of-sale.
- Automating cash handling minimises the risk of errors and shrinkage while enhancing staff productivity and customer service.
- Verification is performed within the device, with no cash exposure.



Introduce automated cash payments as a simple, fast, self-operated process, that delivers accuracy, efficiency and safety to the customer experience.

Pharmacy Store



- "Follow me" LED guidance for deposits
- LED reminder for dispense
- Bulk deposit and dispense for quick operation
- Banknote alignment function in the inlet, to avoid feeding errors
- Fast and accurate cash transactions
- Efficient connections with your partners
- Efficient collection with safe bag

- Reduce collection operations with auto-refill cassettes
- Supports cassette interface with back-office solutions
- Efficient connections with your partners
- Encryption interface for enhanced data security
- Coin auto-refill to reduce replenishment time / cost

BACK OFFICE SOLUTION

Save time and increase back-office efficiency

- Back-office cash recycling solutions accelerate back-office cash processes in high-volume cash locations.
- Delivering increased productivity for your staff and reducing the risk of cash shrinkage, back-office cash recycling allows staff to focus on higher-value activities, that improve customer experience and drive growth for your business.

A secure cash management system that improves back-office efficiency, reduces cash exposure and enhances connections with banks and CIT partners.



- Direct coin dispensing into manual cash drawer
- Extra large recyclable banknote capacity
- Auto verification
- Separate door for CIT partner access
- Closed-loop solution with front-office devices (specific software required)



CASH MANAGEMENT SOFTWARE


Efficient and accurate cash management provides centralised_ remote management of device status in real time

Centralised management:

- Real-time sales and cash flow
- Consolidated "End of Day" across all devices
- Various cash processing reports
- Flexible layout of dashboard

- Remotely manage all devices
- Real-time device status e-mail notifications
- Simulating function for next action
- CI-Connector provides a flexible communication function

CONNECTING YOUR CASH PROCESSES



SPECIFICATIONS – FRONT OFFICE SOLUTION

		FRONT OFFICE			
	CI-10BX		CI-10CX		
Number of recy	cle modules	4 recycle modules	8 recycle modules		
Capacity		100 notes / recycle ¹	Total 8 stackers (Stacker M: 8) 2 EURO 150 coins 0.1 EURO 200 coins 1 EURO 150 coins 0.05 EURO 200 coi 0.5 EURO 150 coins 0.02 EURO 250 coins 0.2 EURO 160 coins 0.01 EURO 350 c *Each capacity is the volume of coins per stacker		
		Collection: 300 notes ¹ (interface cassette type) 450 – 360 notes ¹ (collection cassette type) 450 – 320 notes ¹ (safe bag type)	Coin overflow tray capacity 1,800 coins ² Auto-refill cassette capacity 1,000 coins ²		
Total capacity of banknotes/coins		700 notes ¹ (interface cassette type) 850 – 760 notes ¹ (collection cassette type) 850 – 720 notes ¹ (safe bag type)	Dependent on recycle module configuration		
	Donooit	Capacity of inlet: 30 notes1	Capacity of inlet: 50 coins ²		
Processing	Deposit	Speed of cash in: 3 notes / sec1	Speed of cash in: 5 coins / sec ²		
FIDCessing	Dispensing	Capacity of outlet: 10 notes1	Capacity of outlet: 50 coins ²		
	Dispensing	Speed of cash out: 3 notes / sec1	Speed of cash out: 4 coins / sec ²		
Dimensions (W × D × H)		240 × 485 × 750 – 760mm (9.4" × 19.0" × 29.5" – 29.9") with slide extension unit and spacer M 240 × 485 × 820 - 860 mm (9.4" × 19.0" × 32.3" – 33.9") with slide extension unit and spacer L 240 × 485 × 870 – 960 mm (9.4" × 19.0" × 34.3" – 37.8") Height can be adjusted	240 × 485 × 750 - 760 mm (9.4" × 19.0" × 29.5"- 29.9") with slide extension unit and spacer M 240 × 485 × 820 - 860 mm (9.4" × 19.0" × 32.3" - 33.9") with slide extension unit and spacer L 240 × 485 × 870 - 960 mm (9.4" × 19.0" × 34.3" - 37.8") Height can be adjusted		
Weight		58.2 kg / 128 lbs with spacer M : 64.9 kg / 143 lbs with spacer L : 67.4 kg / 148 lbs Collection cassette type including cassette	49.1 kg / 108 lbs with spacer M : 55.8 kg / 123 lbs with spacer L : 58.3 kg / 128 lbs Collection cassette type including cassette		

1. Dependent on banknote quality. Capacities are for reference only and are not guaranteed. 2. The capacity of coins is calculated in 10 EURO cent.

Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

SPECIFICATIONS – BACK OFFICE SOLUTION

BACK OFFICE			OFFICE		
		CI-100BX	CI-100CX		
Number of recy	cle modules	4 modules	8 recycle stackers		
Capac	. :. .	2,400-2,000 notes ¹ (600-500 notes ¹ /modules) 500 EURO 500 notes ¹ 200 EURO 520 notes ¹ 100 EURO 520 notes ¹ 50 EURO 520 notes ¹ 20 EURO 520 notes ¹ 10 EURO 560 notes ¹ 5 EURO 600 notes ¹ Optional modules: Total 6 or 8 recycle modules	Total 8 stackers (Stacker M: 8) 2 EURO 1,550 coins 1 EURO 1,850 coins 0.5 EURO 1,650 coins 0.2 EURO 2,200 coins 0.1 EURO 3,150 coins 0.05 EURO 3,000 coins 0.02 EURO 3,950 coins 0.01 EURO 5,350 coins *Each capacity is the volume of coins per stacker		
Capac	лту	Collection capacity: Coin overflow box : 1,000 coins ² 3,200-2,500 notes ¹ (stacking safe bag type) Collection : 5,000 coins ² 3,100 notes ¹ (free stacking safe bag type) *The capacity of coins is calculated in 10 EURO cent / 1 US			
Total capacity of banknotes/coins		Dependent on recycle module configuration			
	Denesit	Capacity of inlet: 300 notes1	Capacity of inlet: 600 coins ²		
Processing	Deposit	Speed of cash in: 8 notes/sec1 4 notes/sec1 (interface cassette)	Speed of cash in: 15 coins/sec ³		
Trocessing	Dispensing	Capacity of outlet: 200 notes ¹ Speed of cash out: 8 notes/sec ¹ 4 notes/sec ¹ (interface cassette)	Speed of cash out: 5 coins/sec per stacker ³		
Dimensions (W × D × H)		without monitor UL-291 24-hours safe: 420 × 900 × 1,350 mm (16.5" × 35.4" × 53.1") CEN III / CEN IV safe: 475 × 967 × 1,350 mm (18.7" × 38.1" × 53.1") with monitor (monitor height: 423 mm / 16.7") UL-291 24-hours safe: 420 × 900 × 1,643-1,773mm (16.5" × 35.4" × 64.7" - 69.8") CEN III / CEN IV safe: 475 × 967 × 1,643-1,773mm (18.7" × 38.1" × 64.7"-69.8")	460 × 835 × 1,140 mm (18.1" × 32.9" × 44.9") Optional monitor height adjustable: 1,533-1,664 mm (60.4" – 65,5")		
Weight		530kg / 1,168 lbs. (UL-291 24-hours safe) 730kg / 1,609 lbs. (CEN III safe) 750kg / 1,653 lbs. (CEN IV safe) monitor weight: 9.7kg / 21 lbs	250 kg / 551 lbs Optional monitor weight: 9.7kg / 21lbs		

1. Dependent on banknote quality. Capacities are for reference only and are not guaranteed. 2. The capacity of coins is calculated in 10 EURO cent. 3. The capacity of coins is calculated in 1 EURO cent. Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

SPECIFICATIONS – BACK OFFICE SOLUTION

		BACK OFFICE			
		CI-300BX	CI-300CX		
Number of recyc	cle modules	5 recycling cassette configurations and up to 7 recycling modules	8 recycle stackers		
Сарас	it,	Cassette 1: 1 bin for recycle (2,700-1,400 notes) Total 8 stackers (Stacker M: 8) Cassette 2: 2 bin for recycle (750-290 + 1,050-430 notes) 2 EURO 1,550 coins 1 EURO 1,850 coins 0.5 EURO 1,650 coins 0.5 EURO 1,650 coins 0.05 EURO 1,650 coins 0.05 EURO 3,000 coins 0.02 EURO 3,950 coins Optional modules: Total 5 or 7 recycle modules *Each capacity is the volume of coins per stacker			
Capac	ary	Collection capacity: Coin overflow box : 1,000 coins ² 4,500 - 3,600 notes ¹ (stacking safe bag type) Collection : 5,000 coins ² 3,200 - 2,400 notes ¹ (collection cassette type) *The capacity of coins is calculated in 10 EURO cent / 1 USD cent			
Total capacity of ba	anknotes/coins	Dependent on recycle module configuration			
	Denesit	Capacity of inlet: 300 notes1	Capacity of inlet: 600 coins ²		
Processing	Deposit	Speed of cash in: 12 notes/sec1 4 notes/sec1 (interface cassette)	Speed of cash in: 15 coins/sec ³		
riccessing	Dispensing	Capacity of outlet: 200 notes ¹ Speed of cash out: 12 notes/sec ¹ 4 notes/sec ¹ (interface cassette)	Speed of cash out: 5 coins/sec per stacker ³		
Dimensions (W × D × H)		without monitor UL-291 24-hours safe: 420 × 1,017 × 1,350 mm (16.5" × 40.0" × 53.1") with monitor (monitor height: 423 mm / 16.7") UL-291 24-hours safe: 420 × 1,017 × 1,643-1,773mm (16.5" × 40.0" × 64.7" - 69.8")	460 × 835 × 1,140 mm (18.1" × 32.9" × 44.9") Optional monitor height adjustable: 1,533-1,664 mm (60.4" – 65.5")		
Weight		with monitor (monitor weight: 9.7kg / 21 lbs) UL-291 24-hours safe: 600kg / 1,323 lbs. (stacking safe bag type / collection cassette type)	250 kg / 551 lbs		

1. Dependent on banknote quality. Capacities are for reference only and are not guaranteed. 2. The capacity of coins is calculated in 10 EURO cent. 3. The capacity of coins is calculated in 1 EURO cent. Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

SPECIFICATIONS – SOFTWARE

CI-SERVERX



Interface protocol	HTTPS					
Number of connectable units		Maximum number Registered users	Maximum number Registered drawers	Maximum number Front office devices	Maximum number Back office devices	Typical usage
	Small	20	200	3	1	Small Business Bakery, Cafe
	Middle	200	200	10	1	Mid-Large Grocery Stores
	Large	5,000	1,500	200	20	Amusement Park, Sports Arena, Airport

Related solutions...

CI-5

Specifically designed for smaller retail environments, CI-5 securely automates banknote and coin payments at the point-of-sale.



CI-50B/CI-10CX for the front office

A combined cash recycler solution that removes the need for staff to handle cash at the counter.



CI-Reai

This application enables utilisation of all device functionality, without the need for a full POS integration.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK 🖀 +44 (0)1256 368000 Sales enquiries +44 (0)844 811 2006 🎽 info@uk.glory-global.com 🌐 glory-global.com

BRO-CIX-0523-EURO 2.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, CASHINFINITY, UBIQULAR and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. PostgresQL and the Slonik Logo are trademarks or registered trademarks of the PostgreSQL Community Association of Canada, and used with their permission. Chrome is a trademark of Google LLC. Windows, Windows Server are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. © Glory Global Solutions (International) Limited 2023.

Hardware requirements to operate this software are shown below:

	nem	Requirements	Remarks
CPU		1.4Ghz more x64	
ſ	Vlemory	16GB or more	An environment that meets the
ł	HDD	100GB or more	hardware requirements for Windows Server is required
1	Network	Gigabit or higher LAN	

Required environment		
OS	Windows Server 2019	
Database	PostgreSQL 14	

Client restriction

Google Chrome™, Microsoft Edge, Firefox Browser

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds guoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.