



## Compact self-service kiosk

K22

If you're interested in increasing check size and improving the customer experience the K22 Compact self-service kiosk will deliver. Available in wall mounted, free-standing or counter-top configurations the K22 is suitable for any retail store design. Cash, card and mobile payment options mean all your customers will benefit however they choose to pay.



# More than just hardware, comprehensive software delivers a powerhouse solution guaranteed to deliver.

## What is holding you back?

<b>Dimensions (W x D x H) (base module)</b>	12.32" x 11.42" x 29.53" (313 x 290 x 750 mm)
<b>Weight</b>	39.68 - 44.09 lbs (18 - 20 kg)
<b>Power supply</b>	100-240 VAC, 50/60 Hz
<b>Current consumption</b>	3A
<b>Operating environment</b>	0°C to +40°C, 20 to 80% relative humidity, non-condensing
<b>Storage environment</b>	-20°C to +70°C, 5 to 90% relative humidity, non-condensing
<b>Max. operating altitude</b>	6,562 ft (2000 m)
<b>Material</b>	Steel, aluminum, stainless steel
<b>Protection</b>	IP20, designed for indoor use

<b>PC</b>	Processor Intel Core i5-6500 3.3 GHz or Core i3-8100T 3.1 GHz SSD 128 GB RAM 8GB Connectivity: 4 x USB 3.0, 4 x USB 2.0, 1 x VGA, 1 x HDMI, 2 x, COM, 2 x Gigabit Ethernet, Audio in/out
<b>Screen</b>	LCD touch monitor 22", 517 x 313 x 46 mm, 1920 x 1080 pixels Contrast typ. 1000:1 Brightness typ. 220 nits
<b>Scanner</b>	Type: 2D Optical Resolutions: 4.0 mil (Code 39), 5.0 mil (PDF417), 7.5 mil (Data Matrix)
<b>Printer</b>	Technology: Direct thermal line printing, black/white, 200mm/s Resolution: 180 x 180DPI Max. paper roll diameter: 83 mm End-of-roll sensor
<b>Options Available</b>	EFT: Different preparations available Decorating metal frame Semaphore Foot
<b>Safety certifications</b>	EN62368-1, IEC62368-1, UL62368-1
<b>EMC, EMI certifications</b>	CISPR 32/EN55032 class A, CISPR35/EN55035, IEC/EN 61000-3-2, IEC/EN 61000-3-3 FCC part 15 class B, CAN ICES 003

\*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

## Related solutions...

### CI-Hybrid 15

A slim and flexible solution for installing a cash recycling device at the point of sale.



### CI-50 for front office

The addition of the coin unit (CI-10C) integrates coin handling into a single solution, for handling both notes and coins.



### Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management.



Glory, 3333 Warrenville Road, Suite 310, Lisle, IL 60532 USA

+1 (800) 527-2638 info@us.glory-global.com [glory-global.com](http://glory-global.com)

DS-ACRELECK22-0222/US\_2.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or license save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, ACRELEC and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2022.