



## Self-service kiosk

K27

If you're interested in increasing customer check size and improving the ordering experience look no further than the K27 Self-service kiosk. Ultra-thin, ultra-sleek the K27 is designed to deliver if you're short on space or you want maximum self-service capacity. Cash, card and mobile payment options mean your customers will benefit, however they choose to pay.



# More than just hardware, best-in-class software for content management and easy integration with your POS system delivers the full solution. What is holding you back?

<b>Dimensions (W x D x H)</b>	16.18" x 15.2" x 61.89" (411 x 386 x 1572 mm)
<b>Weight (with/without screen)</b>	110.25 / 94.82 lbs (50kg / 43kg)
<b>Power supply</b>	100-240 VAC, 50/60 Hz
<b>Current consumption</b>	Single-side, wall-mounted: 3A – Double-side: 5A
<b>Operating environment</b>	0°C to +40°C, 20 to 80% relative humidity, non-condensing
<b>Storage environment</b>	-20°C to +70°C, 5 to 90% relative humidity, non-condensing
<b>Material</b>	Steel, aluminum, stainless steel
<b>PC</b>	Processor Intel Core i5-6500 3.3 GHz SSD 128 GB RAM 8GB Connectivity: 4 x USB 3.0, 4 x USB 2.0, 1 x VGA, 1 x HDMI, 2 x COM, 2 x Gigabit Ethernet, Audio in/out

<b>Screen</b>	LCD Multi-Touch Monitor, 10 points 27", 598 x 336 mm, 1920 x 1080 pixels 16.7 million colors Vision angle: Vertical 178° / Horizontal 178° Contrast typ. 1200, min 800 Brightness typ. 270 nits, min 225 nits
<b>Scanner</b>	Type: 2D Optical Resolutions: 4.0 mil (Code 39), 5.0 mil (PDF417), 7.5 mil (Data Matrix)
<b>Printer</b>	Technology: Direct thermal line printing, black/white, 250mm/s Resolution: 203 x 203DPI or 203 x 180DPI Max. paper roll diameter: 83 mm End-of-roll sensor
<b>Options Available</b>	EFT: Different preparations available Camera for facial recognition
<b>Safety certifications</b>	EN62368-1, IEC62368-1, UL62368-1
<b>EMC, EMI certifications</b>	CISPR 32/EN55032 class A, CISPR35/EN55035, IEC/EN 61000-3-2, IEC/EN 61000-3-3 FCC part 15 class B, CAN ICES 003

\*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

## Related solutions...

### CI-Hybrid 15

A slim and flexible solution for installing a cash recycling device at the point of sale.



### CI-100

Fast secure cash processing and storage in the back office.



### Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management.



Glory, 3333 Warrenville Road, Suite 310, Lisle, IL 60532 USA

+1 (800) 527-2638 info@us.glory-global.com [glory-global.com](http://glory-global.com)

DS-ACRELECK27-0222/US\_2.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or license save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, ACRELEC and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2022.