



Self-Checkout Solution

S15

Serve more customers without increasing checkout staff. The S15 is fully customizable with an adaptable design to perfectly fit your stores' layout. Cash, card and mobile payment options mean all your customers will benefit from the enhanced checkout experience however they choose to pay.



More than just hardware, comprehensive software delivers a powerhouse solution guaranteed to deliver. What is holding you back?

Dimensions (W x D x H) (including scale and side table)	58.58" x 28.89" x 82.83" (1488 x 734 x 2104mm)
Weight	242.5lb (scale: 77.16lb, side table: 30.86lb) 110kg (scale: 35kg, side table: 14kg)
Power supply	100-240VAC, 50Hz
Current consumption	7A
Operating environment	0°C to +40°C, 20 to 80% relative humidity, non-condensing
Storage environment	-20°C to +70°C, 5 to 90% relative humidity, non-condensing
Max. operating altitude	6561.68ft (2000m)
Material	Steel, aluminum, stainless steel, plastic
Protection	IP20, designed for indoor use
Panel PC	Processor i3-4330TE, 2.4GHz SSD 128GB RAM 4GB Connectivity: 1 x COM-port (RJ45) with RI / 5V / 12V Selectable, 3 x USB 2.0, 2 x USB 3.0, 1 x 24V-powered USB Port, 1 x cash drawer port RJ11 (12V / 24V), 1 x Gigabit LAN Port RJ45, 2 x video ports 2 x 2W internal speaker
Screen	LCD touch monitor: 15", 1024 x 768 pixels Contrast typ. 1000:1 Brightness typ. 350 nits Projected capacitive touch

Fixed scanner	Type: 2D Optical Resolutions: 5 mil (Code 39), 5 mil (PDF417), 10 mil (Data Matrix), 10 mil (QR Code)
Handheld scanner	Type: 2D Optical Resolutions: 5 mil (Code 39), 6.6 mil (PDF417), 10 mil (Data Matrix), 10 mil (QR Code)
Printer	Technology: Direct thermal line printing, black/white, 250mm/s Resolution: 203 x 203DPI or 203 x 180DPI Max. paper roll diameter: 3.26" (83mm); 60gm < grammage <140gm End-of-roll sensor
Scale (optional)	18.11" 22.87" (460 581mm) 176lb (80kg max), accuracy 0.17lb (10g)
Cash management (optional)	GLORY CI-10 Family
Semaphore	LED illumination, different colors selectable
Side table (optional)	18.11 x 22.04" (460 x 560mm) 30.86lb (14kg)
Safety certifications	EN60950-1
EMC, EMI certifications	EN62311, EN55022 class A, EN52024, EN61000 CISPR 24 / EN 55024, CISPR 32 / EN 55032 class A, EN 61000-3-2, EN 61000-3-3

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CI-10

Compact cash recycling solution, enabling automated cash handling at point-of-sale positions.



CI-100

Fast secure cash processing and storage in the back office.



Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management.



Glory, 3333 Warrenville Road, Suite 310, Lisle, IL 60532 USA

+1 (800) 527-2638 info@us.glory-global.com glory-global.com

DS-S15-0222/US_1.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or license save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, ACRELEC and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2022.