



Compact Self-Checkout Solution

S22 Lite

Designed for smaller stores, the S22 Lite Compact Self-Checkout Solution gives your customers control without sacrificing selling space. Cash, card and mobile payment options mean all your customers will benefit from the enhanced checkout experience however they choose to pay.



More than just hardware, best-in-class management software and easy integration with your POS system delivers the full solution. What is holding you back?

Dimensions (W x D x H) (base module)	35.08" x 12.33" x 9.87" (891.1 x 313.3 x 250.7mm [without semaphore])
Weight	39.68lb (18kg)
Power supply	100-240 VAC, 50/60Hz
Current consumption	3A
Operating environment	0°C to +40°C, 20 to 80% relative humidity, non-condensing
Storage environment	-20°C to +70°C, 5 to 90% relative humidity, non-condensing
Max. operating altitude	6561.68ft (2000m)
Material	Steel, aluminum, stainless steel
Protection	IP20, designed for indoor use
PC	Processor Intel Core i5-6500 3.3GHz SSD 128GB RAM 8GB Connectivity: 4 x USB 3.0, 4 x USB 2.0, 1 x VGA, 1 x HDMI, 2 x COM, 2 x Gigabit Ethernet, Audio in/out
Screen	LCD touch monitor 22", 1920 x 1080 pixels Contrast typ. 1000:1 Brightness typ. 220 nits
Scanner	On-counter high performance barcode reader, 1D/2D Ambient light 0 - 86100 lux Interfaces: OEM (IBM) USB; RS-232; USB Keyboard, USB Com Resolution (max.) 5 mil

Printer	Technology: Direct thermal line printing, black/white, 250mm/s Resolution: 203 x 180DPI Max. paper roll diameter: 3.26" (83mm), thickness 0.06mm~0.1mm Paper-end sensor, paper-near-end sensor
Semaphore	12V RGB LEDs, controlled by USB
Speaker	Speaker linked to PC line-out, 2W
Options Available	EFT: Specific integration on demand Additional foot Wall-mounting adaptation kit Handheld scanner Camera
Safety certifications	EN62368-1
EMC, EMI certifications	CISPR 32/EN55032 class A, CISPR35/EN55035, IEC/EN 61000-3-2, IEC/EN 61000-3-3 FCC part 15 class B, CAN ICES 003

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CI-Hybrid 15

A slim and flexible solution for installing a cash recycling device at the point of sale.



CI-100

Fast secure cash processing and storage in the back office.



Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management.



Glory, 3333 Warrenville Road, Suite 310, Lisle, IL 60532 USA

+1 (800) 527-2638 info@us.glory-global.com glory-global.com

DS-S22LITESCO-1221/US_1.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or license save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, ACRELEC and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2022.