

GLORY

InstaChange™

Coin dispenser

Dealing with coins is time consuming for your staff and prone to errors which impact end of day balancing. InstaChange provides intelligent, accurate and efficient loose coin dispensing allowing you staff to focus on the customer rather than counting coins and reduces operational costs.



InstaChange accelerates the delivery of change to your customers, reduces errors and enhances the experience your customers receive.

Intelligent functionality

InstaChange automatically dispenses the right amount of change back to your customer. And unless you tell it otherwise, InstaChange will always dispense the least amount of coin required. If selected, InstaChange will intelligently substitute for low channels, further extending run-time.

Revolutionary universal design

An innovative design keeps moving parts to a minimum resulting in a lower cost of ownership and increased reliability.

The universal base supports a variety of coin set magazines making it easy for global customers to maximise in-store equipment inventory and minimise service support variations.

Ease of use

InstaChange's tear drop design makes for easy placement. InstaChange can be positioned in any direction to ensure the coin cup is within easy reach of the customer, cashier or teller.

When InstaChange does require refilling, loose or rolled coin is easily loaded into the coin magazine while it sits either on the universal base or flat on a table. Balancing is aided through the use of colour coded calibration labels.

Interfaces

Each unit ships with standard software drivers (OPOS, JPOS) allowing InstaChange to quickly interface with most point of sale systems in use today. InstaChange is also fully compatible with the Glory range of Teller Assist products.

Supported coin sets	Canadian Euro USA
Mounting hardware	Each unit ships complete with installation template and bolt down kit
Connectivity	RS232 and USB as standard
Dimensions (H x W x D)	273 x 190 x 287 mm
Weight	4.5 kg
Power supply	108 – 240V AC (+10%), 50/60 Hz
Power consumption	60W
Manufacturing standards and approvals	ISO9001, CE, UKCA, CUL, Windows XP Approved.
Options	Additional magazines for quick change out

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

WS-30

Compact tabletop coin wrapper, offering a high level of performance and low-maintenance operation.



QC™

A fully-automated, self-service coin deposit solution, allowing customers to quickly and easily deposit coin.



VERTERA™ 6G

Vertera 6G teller cash recyclers deliver a simple, flexible, comprehensive and integrated teller automation solution.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

+44 (0)1256 368000 info@uk.glory-global.com glory-global.com

DS-INSTACHANGE-0521_2.1

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, InstaChange, QC, Vertera and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2021.