

# MultiMech<sup>™</sup> Secure

Multi denomination dispenser

Offering unrivalled security and protection of cash during replenishment due to key locked cassettes, the MultiMech Secure ensures your customers can rely on you to provide secure solutions regardless of location. Delivering the highest levels of uptime and reliability, the MultiMech Secure confidently manages and dispenses worldwide currencies wherever your customers deploy your solutions.



## Its robust design and ease of integration make the MultiMech Secure ideal for almost any dispensing or PayIn/PayOut application.

### **Secure Cassettes**

The MultiMech Secure offers cassettes which can only be opened with the supplied key, allowing for units to be installed in unmanned and remote locations. Additionally, your customer is provided with unrivalled security and protection of cash during CIT and replenishment.

### **Unique Glory Technology**

Intelligent Double Detection, IDD<sup>TM</sup>, provides unbeatable detection of doubles even when notes are severely degraded. This increases the transaction performance and operational efficiency your customers require. No mechanical adjustments are required – IDD is ready to use straight out of the box.

The MultiMech Secure is designed in accordance with the recommendations of leading International Standards Organisations such as RoHS, UL, CE and UKCA to allow for final approval when installed in complete systems.

Speed range	5 notes per second
Speed range	5 notes per second
Document size range	Width: 60 – 82 mm
	Length: 110 – 180 mm
	Thickness: 0.06 – 0.18 mm
Maximum transaction size	50 ATM fit notes delivered note by note (spray dispense)
Capacity	Upper: 150 mm or 1300 banknotes
	Lower: 192 mm or 1700 banknotes
	Reject vault: 50 banknotes
Connectivity	RS232C or USB connection as standard
•	Same communications protocol as NMD050 allowing for plug and play
	compatibility
SNR enabled	Serial Number Recognition is available as an embedded function or
	upgrade which can be enabled
SNR accuracy	Higher than 98%
Power supply	Operates from DC-only supply requiring: 24V ±10% Max load current 3.5A
	*Glory can recommend quality suppliers or UL/CE approved PSU's
Operating environment	Temperature: 10 – 50°C, 50 – 122°F
	Relative humidity: 10 – 85% non-condensing
	*operating time above 45 degrees should be limited to less than 10% of product life
Dimensions (H $\times$ W $\times$ D)	318 × 259 × 320 mm
Weight (without notes)	Without note cassette: 8.5 kg/18.7 lbs
	With note cassettes: 15 kg/33.07 lbs
Manufacturing standards	Designed in accordance with RoHS, UL, CE and UKCA
and approvals	

<sup>\*</sup>Based on new issue banknotes, circulated notes will reduce capacity. The performance of polymer notes may reduce at extreme temperature and humidity combinations. Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by Glory Global Solutions (International) Limited. They may vary depending on usage conditions and are not guaranteed.

### Related solutions...

### **MINIMECH™**

An efficient, easy to maintain, single demonination mechanism offering a compact footprint.



### MULTIMECH™

Easily integrated into almost any self-service solution, the MultiMech offers increased capacity with two cassettes.



### **NMD100**

A high capacity, front or rear bundle delivery module with proven reliability.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

DS-MULTIMECHSECOEM-0621 2.1

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin guality and process used. GLORY, IDD, MiniMech, MultiMech and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. @ Glory Global Solutions (International) Limited 2021.