

Vertera[™] 6G

Teller cash recycler

Whether you're looking to transform your branches or simply improve efficiency for increased profitability, the Vertera 6G will support your strategy. Enabling open plan layouts, reduced start / end of day processes, faster teller transactions, redeployment of staff and enhanced customer experience – the Vertera 6G delivers.



Vertera 6G teller cash recyclers deliver an intuitive, secure, flexible and integrated teller automation solution to address the real needs of your customers and staff.

Roll storage system	8 RSM			
Capacity	Up to 600 notes per RSM			
Touch screen display	7" Touch Screen			
Note handling	Note length: 4" – 7.3" (100 – 185 mm) Note width: 2.2" – 3.5" (55 – 90 mm) Note thickness: 0.002" – 0.007" (0.06 – 0.18 mm) Paper, polymer, composite, tactile feature-note capable			
Note processing speed	Dispense: up to 7 notes per second Deposit: up to 5 notes per second in a single pass			
Users	Unlimited users (subject to software used)			
Machine input and output	Input pocket – up to 250 notes per bundle, unlimited bundles Output pocket – up to 100 notes, unlimited bundles Reject pocket – up to 50 notes, unlimited bundles			
Interfaces	2 USB device ports or 2 serial connections 1 USB host port, to support printer and other peripherals 1 TCP/IP port			
Connectivity	DeviceController™ J/XFS, native driver packages XML interface option CashInsight™ Assure compatibility			
Remote monitoring	UBIQULAR™ Bridge SNMP Agent			

Door configuration	Manual drop deposit door				
Detection	SDA II Defect detection options including TAPE				
Power supply	100 – 240V AC, 47 – 63 Hz				
Power consumption	1.25 kWh typical average daily power consumption (based on 3000 note movements per day)				
Dimensions and weight	Model	Dimensions	Height under desk	Weight	
$(L \times W \times H)$	UL291	37.3" × 18.3" × 31.3" (948 × 465 × 796 mm)		699lbs. (317 kg)	
	Standing configuration: UL291: Add 8.4" (214 mm) height				
Options	Uninterruptible power supply Connectivity to all open network architectures Sitting or standing height configurations CashInsight Assure teller/cashier application UBIQULAR Bridge remote monitoring and management				

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CashInsight[™] Assure

CashInsight Assure facilitates the operation of cash handling devices, providing immediate teller productivity.



UBIQULAR™ Bridge

Continuous performance monitoring and remote device management solution.



InstaChange™

A fast, accurate and secure means to automatically return change to customers.



Glory, 3333 Warrenville Road, Suite 310, Lisle, IL 60532 USA ☎ +1 (800) 527-2638 info@us.glory-global.com glory-global.com

DS-VERTERA6G-0721/US_3.2

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or license save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, CashInsight, DeviceController, InstaChange, UBIQULAR, Vertera and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries.