

GLORY



Semi-outdoor self-service kiosk

K27 Semi-outdoor

If you're interested in expanding your sales footprint and improving operational efficiencies, bring inside outside with the K27 Semi-outdoor self-service kiosk. Designed for durability and security this kiosk helps you stay operational 365 days a year, no matter the weather. Available in two configurations, the K27 Semi-outdoor delivers customer engagement opportunities before they even set foot in your store.



More than just hardware, comprehensive software delivers a powerhouse solution guaranteed to deliver. What is holding you back?

Dimensions (W x D x H)	558 x 268 x 1935 mm (standard model) 500 x 214 x 1114 mm (wall-mounted version)
Weight	97 kg (standard model) 72 kg (wall-mounted version)
Power supply	100-240 VAC, 50/60 Hz
Current consumption	3A
Operating environment	-10°C to +50°C, 20 to 80% relative humidity, non-condensing
Storage environment	-20°C to +70°C, 5 to 90% relative humidity, non-condensing
Installation	Semi-Outdoor: Kiosk must be protected from direct sunlight
Protection	IP55 / PD3
Material	Stainless steel

PC	Processor Intel Core i5 6300U 2.4 GHz SSD 128 GB RAM 8GB Connectivity: 4 x USB 3.0, 4 x USB 2.0, 1 x VGA, 1 x HDMI, 4 x COM, 2 x Gigabit Ethernet, Audio in/out, DIO 8 bits
Screen	LCD Multi-Touch Monitor, 10 points 27", 598.6 x 336.1 mm, 1920 x 1080 pixels 16.7 million colours Vision angle: Vertical 178° / Horizontal 178° Extended temperature range: -20 to +70°C Contrast typ. 1000:1 Brightness typ. 7000 nits Brightness adjustment according to environment light Self-protection against high temperature
Scanner	Type: 2D Optical Resolutions: 4.0 mil (Code 39), 5.0 mil (PDF417), 10 mil (Data Matrix)
Printer	Technology: Direct thermal line printing, black/white, 80mm/s Resolution: 203 dpi Max. paper roll diameter: 120 mm Paper thickness: 59 to 150um (52g/m² to 128g/m²) End-of-roll sensor, paper-near-end sensor
Options available	EFT: Different preparations available
Safety certifications	EN62368-1, EN60950-22
EMC, EMI certifications	EN62311, EN55022 class A, EN52024, EN61000

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

K-27

Ultra-thin, ultra-sleek the K27 is designed to deliver if you're short on space or you want maximum self-service capacity.



K-32 Semi-outdoor

Create high-impact customer engagement with this large screen semi-outdoor kiosk.



Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

+44 (0)1256 368000 Sales enquiries +44 (0)844 811 2006 info@uk.glory-global.com glory-global.com

DS-ACRELECK27/SO-0222_1.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the referenced products and services are continually being developed it is important for customers to check that they have the latest particulars. Although every precaution has been taken in preparation of this document, Glory and any other company identified or referred to in this document accept no responsibility or liability for loss or damages resulting from the use of, or reliance on, the information contained in this document. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities, capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, ACRELEC and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2022.