

GLORY



## Semi-outdoor self-service kiosk

K32

Supersize your impact and increase customer engagement with the K32 Semi-outdoor self-service kiosk. Designed for durability and security, this powerhouse kiosk brings the inside outside and allows customers flexibility 365 days a year, no matter the weather. Fully configurable with a high-impact screen, the K32 Semi-outdoor creates the interactive feel proven to increase revenue and operational efficiency.



## More than just hardware, comprehensive software delivers a powerhouse solution guaranteed to deliver. What is holding you back?

<b>Dimensions (W x D x H)</b>	2134 x 570 x 228.1 mm
<b>Weight</b>	135/115 kg (standard model) 91/71 kg (wall-mounted version)
<b>Power supply</b>	100-240 VAC, 50/60 Hz
<b>Current consumption</b>	3A
<b>Operating environment</b>	-10°C to +40°C, 20 to 80% relative humidity, non-condensing
<b>Storage environment</b>	-20°C to +70°C, 5 to 90% relative humidity, non-condensing
<b>Installation</b>	Semi-outdoor: Kiosk must be protected from direct sunlight
<b>Protection</b>	IPx4
<b>Material</b>	Stainless steel

<b>PC</b>	Processor Intel Core i5 6300U 3 GHz SSD 128 GB RAM 8GB Connectivity: 4 x USB 3.0, 4 x USB 2.0, 1 x VGA, 1 x HDMI, 4 x COM, 2 x Gigabit Ethernet, Audio in/out
<b>Screen</b>	LCD Multi-Touch Monitor, 10 points 32", 1920 x 1080 pixels Colours: 8 bits Vision angle: Vertical 178° / Horizontal 178° Extended temperature range: -20 to +70°C Contrast typ. 4000:1 Brightness typ. 2000 nits, min 1500 nits
<b>Scanner</b>	Type: 2D Optical Resolutions: 4.0 mil (Code 39), 5.0 mil (PDF417), 7.5 mil (Data Matrix)
<b>Printer</b>	Technology: Direct thermal line printing, black/white, 200mm/s Resolution: 203 dpi Max. paper roll diameter: 83 mm End-of-roll sensor
<b>Electronic openings</b>	Electronic management of openings, for printer access, and for maintenance
<b>Options available</b>	EFT: Different preparations available
<b>Safety certifications</b>	EN60950-1, EN60950-22
<b>EMC, EMI certifications</b>	EN62311, EN55022 class A, EN52024, EN61000

\*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

## Related solutions...

### K-27

Ultra-thin, ultra-sleek the K27 is designed to deliver if you're short on space or you want maximum self-service capacity.



### K-27 Semi-outdoor

Create high-impact customer engagement with this flexible semi-outdoor kiosk.



### Professional Services

Transaction analysis, connectivity, advisory services, user training through to full project management.



Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

+44 (0)1256 368000 Sales enquiries +44 (0)844 811 2006 info@uk.glory-global.com [glory-global.com](http://glory-global.com)

DS-ACRELECK32/SO-0222\_1.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the referenced products and services are continually being developed it is important for customers to check that they have the latest particulars. Although every precaution has been taken in preparation of this document, Glory and any other company identified or referred to in this document accept no responsibility or liability for loss or damages resulting from the use of, or reliance on, the information contained in this document. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities, capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY, ACRELEC and their associated graphical representations are each a trademark or a registered trademark of GLORY LTD. Group of Companies in the EU, the U.S. and other countries. © Glory Global Solutions (International) Limited 2022.